The Biggest Thing in **Small HD Monitors**

LCD-703HDA LCD-703HDV



LCD- 703HDA Unit with Anton Bauer QRC - Gold mount



LCD- 703HDV Unit with "V" lock mount for IDX batteries

Active Matrix 7" Color LCD Monitors

- HD compatible (supports 480p/i, 576p/i, 720p, 1080p/i) Both component & DVI inputs accept 1080p/i.
- LED backlight provides longer life, uses less power and provides better color saturation
 - RS-232 feature allows external devices to control the monitor through the serial port.
 - Underscan capability
 - Blue gun feature provides for easy adjustment of screen display
 - DVI-D input jacks accepts digital input.
 - Anti-glare treatment adds to viewing pleasure
 - Displays either 16:9 or 4:3 aspect ratio
 - Front controls for : menu, up, down, On/Off, mode
 - IR remote control
 - · Case made of durable metal.
 - A/C adaptor (Part No. AC-1000) included
 - · Built-in interface and proper cable exiting for wall or arm mounting VESA 75mm FPMPMI compliant
 - Response time: 22mS (Rising), 35mS (Falling)
 - Mounting pad with ¼-20 threaded socket (located at bottom and can be moved to top).
 - Runs 16.5 hours on IDX Endura 7S battery.
 - Runs 22 hours on Anton Bauer Dionic 90 battery.





Display: 7" TFT LCD active matrix

Back Light: LED

Input Signal: NTSC/PAL (auto sensing) Resolution: 800 (H) x 480 (V) dots Dot Pitch: 0.19(H) x 0.19(V)mm Brightness rating: 350 cd/m² (Nit)

Contrast Ratio: 300:1 Number of Pixels: 1.2 M

Viewing angle L/R/T/B: 65/65/55/60 degrees

Pixel Configuration: Stipe

Power Requirements: 6~20 VDC, 500mA, + pin, - ground Power Consumption: 350mA@ 12 VDC (max)

Video Input Level: 1.0 V P-P (positive) 75 Ohm LCD-703HDA/HDV: Dimensions (WHD): 174 x 134 x 35mm / 6.9" x 5.3" x 1.4"

(Height including 5mm mounting pad: 134 + 5mm = 139mm)

Actual visible screen size (WH): 152.4 x 91.4mm / 6" x 3.6" Operating temperature: $10 \sim 104^{\circ}F / -12 \sim 40^{\circ}C$

Storage temperature: $-13 \sim 140^{\circ}F / -25 \sim 60^{\circ}C$ Rear inputs: BNC composite video IN/OUT,

S-Video IN/OUT, BNC component IN/OUT RS-232, Tally, DVI-D, 2.1mm DC IN jack

LCD-703HDA / HDV: Weight: Net: 0.7 kg./ 1.5 lbs Gross: TBD

Custom Tote Bag

Order TB-703AV for nylon tote bag with sun sheild.



Metal Sun Sheild SS-703HD

HS-1 Hot shoe mount MB-3 Desk stand SS-703HD Sun shield Custom Tote bag with sun shield for LCD-703HDA and LCD-703HDV. WM-30 Wall mount bracket (fixed)

Optional Accessories

http://www.totevision